Incompressible Fluid flow through free and porous areas

Mohamed Saif Aldien¹ , Hussam.M.Gubara²

¹Turabah University College , Taif University
P. O. Box 888, Zip Code 21974, Kingdom of Saudi Arabia

¹ Academy of Engineering and Medical Sciences, Khartoum, Sudan

²Faculty of Mathematical Sciences and Statistics, AlNeelain University, Khartoum, Sudan

Abstract:

In this paper we discussed incompressible fluid flow problem through free and porous areas by using Darcy's law and continuity equation, by apply the boundary conditions required to specify the solution

Keywords: Incompressible fluid, Darcy's law, continuity equation, pressure, velocity

1-Introduction:

Consider a porous sphere of a radius a with constant permeability k , its centre coincides with the coordinate origin, concentric with another spherical shell with inner radius b ($b > a$) (Saif Aldien 2017). Consider a viscous incompressible fluid with low Reynolds number moves uniformly with constant velocity U past the body, and that the porous regions saturated with the fluid (Clattery 1967). Boundary conditions provide information about the behavior of the solution at physical boundaries of the domain (Quintard and Whitaker 1994). In general three types of the boundary conditions are distinguished (Hilfer 1998) 1. Dirichlet boundary conditions specify the values of

the solution at a given part of the boundary; 2. Neumann boundary conditions specify the value of the spatial derivative of the solution. In the case of flow in porous media, this type of condition is usually written in terms of the fluid flux in the direction normal to the boundary; 3-(Mokadam 1961). Robin boundary conditions, which specify a relationship between the value of solution and its derivative, and can be viewed as a generalization of both Dirichlet and Neumann boundary conditions (Dagan 1989). The boundary conditions required to specify the solution are: 1-The continuity of pressures of different regions at the interface boundary. 2- The continuity of normal velocities.

$$3- \quad -\beta(u_\theta - q_\theta) = \frac{\partial u_r}{\partial r} + \frac{1}{R_\theta} \left[\frac{\partial u_r}{\partial \theta} - u_\theta \right] \text{ at } r = b \quad \text{and}$$

$$\beta(u_\theta - q_\theta) = \frac{\partial u_\theta}{\partial r} + \frac{1}{R_\theta} \left[\frac{\partial u_r}{\partial \theta} - u_\theta \right] \text{ at } r = a$$

Where $\beta = \frac{\alpha}{\sqrt{k}} R_\theta$ is radius of curvature

4-The flow of each fluid can be described by the extended Darcy formula including the relative permeability coefficient.

5-Both fluid phases are barotropic, i.e. each phase density depends only on the pressure in the respective phase (Brenner 1980)

2- Mathematical formulation:

The porous regions (regions 1 and region 3) apply Darcy's law

$$q = -\frac{k}{\gamma} \nabla p \quad (1)$$

Together with the continuity equation

$$\nabla \cdot q = 0 \quad (2)$$

Assume a trial solution in the form

$$\varphi(r, \theta) = \mu U g(r) \cos \theta \quad (3)$$

The velocity components

$$\begin{aligned} u_r &= U \left[1 + \frac{A}{r^3} + \frac{B}{r} + Dr^2 \right] \cos \theta \\ u_\theta &= -U \left[1 - \frac{A}{2r^3} + \frac{B}{2r} + 2Dr^2 \right] \sin \theta \end{aligned} \quad (4)$$

Then the pressure is given by

$$p(r, \theta) = p_\infty + \gamma U \left[Er + F \frac{1}{r^2} \right] \cos \theta \quad (5)$$

Where E and F are arbitrary constants

3- Mathematical Solution:

To specify the pressure for region 1 and 3, we have to take into consideration the following conditions:

$$|g(r)| \rightarrow 0 \quad \text{as } r \rightarrow \infty$$

$$|g(r)| < \infty \quad \text{as } r \rightarrow 0 \quad (6)$$

Now from 5 and 6 we have the pressure for regions 1 and 3 given respectively by:

Region 1 :

$$p(r, \theta) = p_\infty + \gamma U E r \cos \theta$$

Region 3:

$$p(r, \theta) = p_\infty + \gamma \left[\frac{U F}{r^2} \right] \cos \theta \quad (7)$$

Now from spherical polar coordinates

$$\nabla p = \frac{\partial p}{\partial r} i_{-r} + \frac{1}{r} \frac{\partial p}{\partial \theta} i_{-\theta}$$

And

$$q = i_{-r} q_r + i_{-\theta} q_\theta \quad (8)$$

Where i_{-r} and $i_{-\theta}$ are local unit vectors.

Comparing equations 1 and 8 we have

$$\begin{aligned} q_r &= -\frac{k}{\mu} \frac{\partial p}{\partial r} \\ q_\theta &= -\frac{k}{r \mu} \frac{\partial p}{\partial \theta} \end{aligned} \quad (9)$$

By using equations (7) and (9) the velocity field for regions 1 and 3 given respectively by :

Region 1:

$$q_r = -k E U \cos \theta$$

$$q_\theta = k E U \sin\theta \quad (10)$$

Region 3:

$$q_r = \frac{2kF}{\mu} U \cos\theta$$

$$q_\theta = \frac{2kF}{r^2} \sin\theta$$

To find the constants A,B,D,E and F we apply the boundary conditions between regions I and II at $r = a$, and between regions II and III at $r = b$

Matching boundary conditions between regions I and II ($r = a$) we have the following

$$\begin{aligned} u_r(r, \theta) &= q_r(r, \theta) \\ &\rightarrow A + a^2B + a^5D \\ &\quad + ka^3E = -a^3 \end{aligned}$$

$$\begin{aligned} p_I(r, \theta) &= p_{II}(r, \theta) \\ &\rightarrow B + 10a^3D \\ &\quad - a^3E = 0 \end{aligned}$$

$$\begin{aligned} \beta(u_\theta - q_\theta) &= \frac{\partial u_\theta}{\partial r} + \frac{1}{R_\theta} \left[\frac{\partial u_r}{\partial \theta} - u_\theta \right] \\ &\rightarrow \end{aligned}$$

$$\begin{aligned} (2\beta a - 10)A - \beta a^3B - (6a^3 + 4\beta a^6)D - 2\beta a^4E &= 2\beta a^4 \end{aligned} \quad (11)$$

Matching boundary conditions between regions II and III ($r = b$) we have the following

$$\begin{aligned} u_r(r, \theta) &= q_r(r, \theta) \\ &\rightarrow A + b^2B + a^5D \\ &\quad - 2kF = -b^3 \end{aligned}$$

$$\begin{aligned} p_I(r, \theta) &= p_{II}(r, \theta) \\ &\rightarrow B + 10b^3D - F \\ &= 0 \end{aligned}$$

$$\begin{aligned} -\beta(u_\theta - q_\theta) &= \frac{\partial u_r}{\partial r} + \frac{1}{R_\theta} \left[\frac{\partial u_r}{\partial \theta} - u_\theta \right] \\ &\rightarrow \end{aligned}$$

$$\begin{aligned} (2\beta b - 10)A - \beta b^3B - (4\beta b^6 - 6b^5)D + 2kbF - 2\beta BF &= 2\beta b^4 \end{aligned} \quad (12)$$

By Solve equations (11) and (12) to get the value of the constants A , B, D, E, F

4- Conclusion :

In this problem of viscous fluid flow past liquid shell embedded we have three regions (porous regions I, III and free region II) by Applying the boundary conditions by considering the continuity of pressures and normal velocities at the interface boundaries and in addition taking into consideration that the difference of tangential velocities of different flow regimes are proportional to the rate of strain tensors . and get pressure and velocity

5- References :

Brenner, H, (1980) Dispersion resulting from flow through spatially periodic porous media,” Trans R Soc, Vol. 297, No. 1430, , pp. 81–133

Clattery, J. C , (1967) Flow of Viscoelastic Fluids Through Porous Media,” AIChE J., Vol. 13, , pp. 1066–1071.

Dagan, G, (1989) Flow and Transport in Porous Formations, Springer-Verlag, Heidelberg Berlin New York,

Hilfer R ,(1998) Macroscopic equations of motion for two-phase flow in porous media,” Physical Review E, Vol. 58, No. 2, , pp. 2090–2096

Mokadam, R. G, (1961)

Thermodynamic Analysis of the Darcy Law,” Journal of Applied Mechanics, Vol. 28, No. 2, , pp. 208–212

Quintard, M. and Whitaker S ,(1994)

Transport in Ordered and Disordered Porous Media IV: Computer Generated Porous Media for Three-Dimensional Systems,” Transport in Porous Media, Vol. 15, , pp. 51– 70

SaifAIDienM, (2017) Flow Past A Spherical Liquid Drop Embed in Infinite Medium, Mathematics Applied in Science and Technology. ISSN 0973-6344 Volume 9, Number 1) pp 31-34 © Research India Publications.

<http://www.ripublication.com>.

.